



PCB LAYOUT/TOP VIEW

XW-66-SMT-28 3U"/6U"/15U"/30U"/50U"



- NOTES:
- ELECTRICAL:
- 1. VOLTAGE RATING : 125 VAC RMS.
 - 2. CURRENT RATING : 1 AMP.
 - 3. CONTACT RESISTANCE : 30 MILLIOHMS MAX
 - 4. INSULATION RESISTANCE : 500 MEGOHMS MIN @ 500 NDC.
 - 5. DIELECTRIC STRENGTH : 1000 VAC RMS 50Hz or 60Hz, 1MIN.
- MECHANICAL:
- 1. HOUSING & INSERT MATERIAL : PA9T UL94V-0.
 - 2. CONTACT MATERIAL : DIAMETER: 3.5MM PHOSPHOR BRONZE GOLD PLATING OVER NICKEL.
 - 3. SHIELD : 0.20" 0.25MM THICKNESS BRASS WITH TIN PLATED.
 - 4. MATTING/UNMATTING FORCE : 2.2KG. F MAX.
 - 5. RETENTION STRENGTH : 7.7KG. F MIN BETWEEN JACK AND PLUG.
 - 6. OPERATING LIFE : 750 CYCLES MIN.
- ENVIRONMENTAL:
- 1. STORAGE : -40°C ~ +85°C RELATIVE HUMIDITY < 70%
 - 2. OPERATION : -40°C ~ +85°C



东莞市迅旺电子科技有限公司
DongGuan XunWang Electronic Technology Co., Ltd.

Scale: None
Units: mm
Rev: A
Draw: Kal
Approved: Ansom

Unless otherwise stated otherwise tolerances as follows
.XXX ±0.10 .XX ±0.25 .X ± 0.35
ANG ±3°

name: 8321 6P6C-SMT 铁脚直立
Part number: XW-66-SMT-28

Tel: 0769-85398667 Fax: 0769-85384545 Http://www.dgxunwang.com



Page: 1/1

File Name:

E:/XUNWANG/工程图